



ISOLOCORK
ORIGINAL PORTUGUESE CORK
Highest Quality

Best solutions come naturally!

Cork filler is an indoor or outdoor coating for those who need humidity insulation, remove cracks and repair damaged walls due to minor paint defects. Excellent thermal insulation, breathable and water repellent.

Very easy and quick to apply, this product is the best solution for anyone who has cracks.

Projection application, no need to change door and window sills, remove water pipes, etc.

Can be applied on curved surfaces, chimneys and on almost any surface (cement, wood, metal, etc.), it is an excellent fire barrier and does not release toxic smoke.

Available in a wide variety of colors, this finish emphasizes texture, flexibility, speed of application, simplicity and versatility.

This material should not be applied at temperatures below 5 ° C and above 30 ° C.

Apply avoiding direct sun, rain or frost. The surface to be applied must always be clean and dry. Do not apply on glazed surfaces.

Contact Details:

Zona Industrial de Sam, Rua da Ferveça, building 1 - 17
Apt. 7020 4764-908 Ribeirão - V. N. Famalicão PORTUGAL
Office: +351 252.491 859 - +351 962 697 670
www.isolocork.com - email: jorgesa@isolocork.com

Just mix cork with binder for 2 minutes...
and, that's it. Ready to apply.



Specs

Appearance	Viscous appearance - paste
Color	Ral colors available
Density	0,82 +/- 0,20 g/cm3
Storage	12 months in original packaging in dry place and protected from the sun
Drying time	4 to 6 hours between coats 12 to 24 hours final drying
Yield	650 grams/coat
Application Temperature	5°C to 30°C
Thermal Conductivity	0,061 W/m.K ISO 8301:1991
Water vapor permeability	2,97 EN ISO 7783:2011
Accelerated aging	Adapted to the ASTM G 53 norm
Flexion strain rupture	3.15 Mpa
Compression strain rupture	6.5 Mpa
Water absorption coefficient	0,1 kg/(m2,min0.5)
Adhesion ceramic brick	0,4 N/mm2
Adhesion cement block	0,6 N/mm2

Any color available



base for light, medium and dark colors,
so you can pigment yourself.



SOLUTIONS TO GET THE JOB DONE



GUARANTEED
ORIGINAL BRAND
— ORIGINAL PORTUGUESE CORK —
ISOLOCORK[®]
REGISTERED TRADEMARK FROM PUBLICIPLO COMPANY
Highest Quality

ISOLOCORK insulation ideas

ISOLOCORK FILLER
3mm thick for indoor and outdoor applications where the main need is humidity insulation and eliminate fissures.
Product designed for quick and easy application on any type of façade.
Any color available. Unlike ETICS coatings, you do not need to change door sills and windows.



Beautiful Design
Comes to Life
with
Simple Solutions

